

 Working Height Max.
 18 m (59')

 Overall Lift Capacity Max.
 680 kg (1,499 lb)


 Overall Width
 2.29 m (7'6")


 Overall Length
 4.88 m (16')

 Overall Weight
 8,900 kg (19,621 lb)

## LS1623ERT Rough Terrain Scissor Lift - Electric Drive

## LS1623ERT SPECIFIATIONS >>>







DIMENSIONS	
A. Working Height Max.	18 m (59')
B. Platform Height Max.	16 m (52'6")
C. Platform Height (Stowed)	2.1 m (6'10")
D. Platform Length	4.2 m (13'9")
E. Platform Width	1.82 m (5'11")
F. Extension Deck (Roll Out)	1.25 / 1.25 m (4'1" / 4'1")
G. Overall Length	4.88 m (16')
H. Overall Width	2.29 m (7'6")
I. Stowed Height (Rails Up)	3.2 m (10'6")
J. Stowed Height (Rails Down)	2.44 m (8')
K. Wheelbase	2.9 m (9'6")
L. Ground Clearance (Pothole Raised/Deployed)	0.36 m (1'2")

PRODUCTIVITY	
Overall Lift Capacity Max.	680 kg (1,499 lb)
Extension Deck Capacity	230 kg (507 lb)
Platform Occupancy Max. (Indoor/Outdoor)	4
Drive Speed (Stowed)	6 km/h (3.7 mph)
Drive Speed (Raised)	1 km/h (0.6 mph)
Turning Radius (Inside/Outside)	4 / 7 m (13' / 22'11")
Lift/Lower Time	80 / 70 s
Gradeability	40 %
Tilt Sensor Activation	X 2° / Y 3°
Outrigger Leveling Angle	X 12° / Y 7°
Tire Size	33 x 12 - 20 mm (1.2" x 0.47" x 0.78")

POWER	
Battery	8 x 6 V / 450 Ah
Charger	48 V / 60 A
Lift Motor	4 x AC 32 V / 3.3 kW
Drive Motor	AC 48 V / 10 kW
Hydraulic Tank Capacity	60 L (15 gal 6 pt)
WEICHT	

WEIGHT	
Overall Weight	8.900 kg (19.621 lb)